

Tron 40S MkII

Float-free EPIRB



- Best global sales and support network
- Antenna mounted LED for increased visibility
- Only EPIRB with heating bracket
- 5 year warranty

Tron 40S MkII

A float-free EPIRB

Tron 40S MkII has improved flash visibility when activated. It is the only EPIRB offered with a heating bracket. Tron 40S MkII is incorporated into the Jotron recycle program.

Technical specifications

PARAMETER	
Battery	Lithium metal, 7.2 V/7200 mAh, 5 year service life
Dimensions	Height: 379 mm, diameter: 180 mm
Weight	2 kg
Materials	Glass reinforced polycarbonate
Compass safe distance	1.5 m
Temperature range	Operating: -20°C to +55°C Storage: -30°C to +65°C
Operating life	Minimum 48 hours at -20°C
Antenna	Omnidirectional
Cospas-Sarsat transmitter	
Frequency	406.037 MHz
Output power	5 W
Homing transmitter	
Frequency	121.500 MHz
Output power	Up to 100 mW
Protocols	Maritime, serialized, radio call sign
ACCESSORIES	
Brackets	FBH-42 heating bracket FB-6 bracket with protective cover
Battery	Replacement kit
Hydrostatic release	HRU kit
WARRANTY	5 year from factory

Tron 40S MkII EPIRB
(Part number 83050)



Tron 40S MkII EPIRB package
(Part number 83050P-01)

Includes:
Tron 40S MkII EPIRB
(Part number 83050)
FB-6 bracket with protective cover
(Part number 85216)

Tron 40S MkII with FBH-42 heating bracket
(Part number 103360)

Includes:
Tron 40S MkII EPIRB
(Part number 83050)
Spare FBH-42 bracket
(Part number 103340)



Approved:



v. 9 Jotron AS reserves the right to change any content herein without notice